

HVAC MOTORS

HP: 1/8 - 2

Frame: 48-56

RPM: 1800

Pole: 4

Volt: 208-230/460V
115/230V

Body: Resilient Cradle



Standard Features :

- Belt Drive - Resilient Cradle
- CSA Approved
- High Start Torque
- Sealed Ball Bearings
- Open Drip Proof
- High Efficiency
- 1725 RPM
- 40° C Ambient Temp Rating
- Class F Insulation
- 18 Month Warranty



Single Phase

HP	Sync. Speed	Model Number	Motor Type	List Price
1/8	1800	BL1-RS-OP-48-4-B-C-.12-RS-SP	SP	260
1/4	1800	BL1-RS-OP-48-4-B-C-.25-RS-CI	CSIR	374
1/3	1800	BL1-RS-OP-56Y-4-B-C-.33-RS-CI	CSIR	397
1/2	1800	BL1-RS-OP-56Y-4-B-C-.5-RS-CC	CSCR	458
3/4	1800	BL1-RS-OP-56-4-B-C-.75-RS-CC	CSCR	477
1	1800	BL1-RS-OP-56-4-B-C-1-RS-CC	CSCR	533
1.5	1800	BL1-RS-OP-56-4-B-C-1.5-RS-CC	CSCR	570

* CI = Single Capacitor Design

CC= Dual Capacitor Design

Three Phase

HP	Sync. Speed	Model Number	List Price
1/3	1800	BL3-RS-OP-56-4-B-D-.33-RS	270
1/2	1800	BL3-RS-OP-56-4-B-D-.5-RS	299
3/4	1800	BL3-RS-OP-56-4-B-D-.75-RS	334
1	1800	BL3-RS-OP-56H-4-B-D-1-RS	397
1.5	1800	BL3-RS-OP-56H-4-B-D-1.5-RS	433
2	1800	BL3-RS-OP-56H-4-B-D-2-RS	477

SP= Split Phase



2015:1