

CRUSHER DUTY

HP: 75 - 250

Frame: 365T - 449T

RPM: 1200/1800

Pole: 4 & 6

Volt: 460V

Body: T-Frame



Standard Features :



- NEMA Design C
- 6 Lead - 460V
- Drive-end Roller Bearing
- Oversized Bearings on DE & ODE
- 1.15 Service Factor
- 40° C Ambient Temperature Rating
- All Position Mounting Ready
- VPI Lap Wound Coil
- Wye-Delta Start Wound
- 4140 Carbon Steel Shaft
- Zerk Fitting Regreaseable Bearing
- Full Cast Iron Construction
- Double Lip Oil Seals on DE & ODE
- Rubber Slinger
- Split Conduit Box is 90° Rotatable
- F1 to F2 Field Convertible (Shipped F1)
- Shear Stabilized Polyurea Grease
- Class F Insulation with Class H Stator
- EISA Compliant
- 24 Month Warranty from Purchase Date

HP	Sync. Speed	Model Number	LRT	List Price
75	1800	OR3-CI-TF-365T-4-RR-E-75	331%	6,229
	1200	OR3-CI-TF-405T-6-RR-E-75	275%	7,525
100	1800	OR3-CI-TF-405T-4-RR-E-100	219%	7,698
	1200	OR3-CI-TF-444T-6-RR-E-100	210%	10,765
125	1800	OR3-CI-TF-444T-4-RR-E-125	269%	11,460
	1200	OR3-CI-TF-445T-6-RR-E-125	217%	12,870
150	1800	OR3-CI-TF-445T-4-RR-E-150	222%	14,111
	1200	OR3-CI-TF-447T-6-RR-E-150	236%	15,255
200	1800	OR3-CI-TF-447T-4-RR-E-200	243%	17,188
	1200	OR3-CI-TF-449T-6-RR-E-200	241%	20,114
250	1800	OR3-CI-TF-449T-4-RR-E-250	228%	19,733



**LIFT
STRAP
INCLUDED**

2014:2