

Washdown Duty

HP: 1/3 - 15
Pole: 2 / 4 / 6

Frame: 56C - 215T
Volt: 208-230/460V

RPM: 1200/1800/3600
Body: T / TC Frame



Standard Features :



- IP 56 Rated Protection
- 50/60 Hz Capable
- 1.15 Service Factor
- 9 Lead Dual Voltage
- Double Lip Oil Seals on DE & ODE
- Inverter Rated 15:1 Constant Torque for VFD use
- Multi-mount Removable Feet
- F1, F2, F3 Field Convertible (Shipped F1)
- Class F Insulation System (Class H Stator)

- One-Way Brass Condensation Drains on DE & ODE
- Designed to Class B Temperature Rise
- Drive End Bearing Locks
- VPI Insulated Windings
- EISA Compliant
- 24 Month Warranty

*** Fully Potted
Conduit Entry**



Models listed in Blue are High Efficiency

HP	SYNC SPEED	Model Number	List Price	
			Rigid Base	C-Face
1/3	3600	WH3-AL-TF-56C-2-B-D-33	--	450
	1800	WH3-AL-TF-56C-4-B-D-33	--	443
1/2	3600	WH3-AL-TF-56C-2-B-D-5	--	465
	1800	WH3-AL-TF-56C-4-B-D-5	--	457
3/4	3600	WH3-AL-TF-56C-2-B-D-75	--	484
	1800	WH3-AL-TF-56C-4-B-D-75	--	482
1	3600	WH3-AL-TF-56C-2-B-D-1	--	499
	1800	WH3-AL-TF-56C-4-B-D-1	--	522
	1800	WH3-AL-TF-143T-4-B-D-1	641	693
	1200	WH3-AL-TF-145T-6-B-D-1	694	746
1.5	3600	WH3-AL-TF-56C-2-B-D-1.5	--	514
	1800	WH3-AL-TF-56C-4-B-D-1.5	--	562
	3600	WH3-AL-TF-143T-2-B-D-1.5	663	715
	1800	WH3-AL-TF-145T-4-B-D-1.5	678	730
	1200	WH3-AL-TF-182T-6-B-D-1.5	857	961
2	3600	WH3-AL-TF-56C-2-B-D-2	--	529

HP	SYNC SPEED	Model Number	List Price	
			Rigid Base	C-Face
2	1800	WH3-AL-TF-56C-4-B-D-2	--	602
	3600	WH3-AL-TF-145T-2-B-D-2	711	763
	1800	WH3-AL-TF-145T-4-B-D-2	710	762
	1200	WH3-AL-TF-184T-6-B-D-2	953	1057
3	3600	WH3-AL-TF-56C-2-B-D-3	--	605
	3600	WH3-AL-TF-182T-2-B-D-3	948	1052
	1800	WH3-AL-TF-182T-4-B-D-3	936	1040
5	1200	WH3-AL-TF-213T-6-B-D-3	1292	1425
	3600	WH3-AL-TF-184T-2-B-D-5	1011	1115
	1800	WH3-AL-TF-184T-4-B-D-5	1019	1123
7.5	1200	WH3-AL-TF-215T-6-B-D-5	1566	1699
	3600	WH3-AL-TF-213T-2-B-D-7.5	1394	1527
10	1800	WH3-AL-TF-213T-4-B-D-7.5	1408	1541
	3600	WH3-AL-TF-215T-2-B-D-10	1541	1674
15	1800	WH3-AL-TF-215T-4-B-D-10	1554	1687
	3600	WH3-AL-TF-215T-2-B-D-15	2147	2216

2014.1